

ALFA NG 265

115 V / 60 Hz

SELF-CONTAINED ICE CUBE MACHINE

FEATURES

- ▶ PRODUCES SOLID GOURMET CRYSTAL CLEAR ICE CUBES
- ▶ A3S: ANTI-SCALE SPRAY SYSTEM. ITV PATENTED SPRAY SYSTEM WITH FLEXIBLE NOZZLES THAT AVOID LIMESCALE DEPOSITS WITH SMALL VIBRATIONS
- ▶ STIF: STRONG INOX FRAME. SOLID MACHINE STRUCTURE IN 4 COLUMNS WITH AISI 304 STAINLESS STEEL FRAME.
- ▶ STRONGEST DOOR IN THE MARKET. MADE OF STAINLESS STEEL. OPENING AND DAMPING SYSTEM PATENTED BY ITV.
- ▶ FRONT VENTILATION CONCEPT: FRONTAL IN-OUT AIR SYSTEM ALLOWS 'BUILT IN' MACHINES
- ▶ CLEANING SWITCH: ALLOWS CIRCULATION OF WATER WITH DESCALING PRODUCT (CALCLIN OR SIMILAR) WITHOUT COOLING.
- ▶ "NEVER STOP" MOTOR PUMP DEVELOPED BY ITV. PUMP WITHOUT SEALS, WHICH AVOIDS DETERIORATION IN HARD WATER
- ▶ EASI: EASY ACCESS FOR SERVICE & INSTALLATION. ALL PANELS CAN BE DISASSEMBLED SEPARATELY.
- ▶ ON/OFF LIGHTED ROCKER SWITCH IN FRONT PANEL
- ▶ TROPICALIZED MACHINES (T CLASS) / HEIGHT ADJUSTABLE LEGS FROM 4.1" TO 0.2"



	 24 H	 70°F/21°C 50°F/10°C lbs (Kg)	 90°F/32°C 70°F/21°C lbs (Kg)	 lbs (Kg)	 in (mm)	 in (mm)	
ALFA NG 265 A		260 (118)	202 (92)	132 (60)	Width 28.15"(715) Depth 27.56"(700) Height* 41.34"(1050)	Width 31.11"(790) Depth 30.32"(770) Height 46.46"(1180)	ALFA 17/21cc
ALFA NG 265 W		275 (125)	216 (98)				1.5" (W) x 1" (D) x 1.2" (H) 39 mm (W) x 27 mm (D) x 30 mm (H) Average dimensions

* WITH LEGS 45"/47"

ACCESSORIES

INCLUDED




NOT INCLUDED (OPTIONAL)




TECHNICAL SCHEME

ALFA NG 265


RIGHT SIDE VIEW




FRONTAL VIEW



LEFT SIDE VIEW



REAR VIEW



* All dimensions in inches (and mm)

OPERATING CONDITIONS

PRODUCTION (LBS) 60Hz


±10% V

41°F/109°F

41°F/95°F

14.5 psi (1 bar) / 87 psi (6 bar)

72 Ice cubes/cycle



24 H

ALFA NG 265 AIR COOLED

	50° 10°	60° 15°	70° 21°	86° 30°
50° 10°	274	256	236	212
68° 21°	260	242	224	200
90° 32°	236	220	202	178
109° 43°	204	188	170	140

24 H

ALFA NG 265 WATER COOLED

	50° 10°	60° 15°	70° 21°	86° 30°
50° 10°	290	271	252	227
68° 21°	275	256	240	214
90° 32°	250	233	216	190
109° 43°	216	199	182	150

MODELS

ALFA NG 265 A

ALFA NG 265 W

	ASHRAE CONDITIONS (BTU/h) (W)	(W) 109°F	(AWG/mm²) (n.)	FUSE	100lbs 90°F / 70°F (Kwh/100 lbs)	gal 100lbs (l/h)	HEAT REJECTED (BTU/h) (W)	(lbs)	(lbs)
ALFA NG 265 A	10,639 3,118	1,150	14/1.5 3	20	9.3	53 22	8,373 2,454	209	225
ALFA NG 265 W	10,639 3,118	1,150	14/1.5 3	20	8.8	194 85	8,373 2,454	209	225

ITV ICE makers

ITV Ice Makers, Inc.
9550 Satellite Blvd, Suite 100
Orlando, FL 32837
Phone: 1 407 826 1860 | Fax: 1 407 826 1861
Toll Free: 1 888 488 1423
sales@itvice.com | www.itvice.com

TECHNICAL ASSISTANCE
ITV ice makers SERVICE

SERVICE
service@itvice.com
Skype: service@itvice.com
PHONE: +1 888 488 1423
FROM 8AM TO 5PM EST

3 YEARS
WARRANTY
PARTS & LABOR

2 ADDITIONAL YEARS
ON COMPRESSOR &
EVAPORATOR
Read our warranty policy
to know more about
limitations and exclusions

NSF

ETL
LISTED
Intertek

SPRAY SYSTEM